



BioD-Watl™ 9

Lightly packed coir wattles for sediment control

Completely Wildlife Safe!

Description

This is to certify that the BioD-Watl™ 9 coir wattles are 9 in (23 cm) diameter cylindrical shape rolls to filter sediment. The knotted high strength outer netting is made from high strength machine spun bristle coir twines. The outer net has 2 in x 2 in (5 cm x 5 cm) openings and has of 60 lbs. (267 N) strength. They are lightly packed with cleaned mattress coir fiber in a uniform manner to filter sediment effectively. The BioD-Watl™ 9 is available in 15 ft. long sections. BioD-Watl™ 9 coir wattles are manufactured to conform to the following properties:

Specifications

Property	BioD-Watl™ 9
Unit Weight	1.5 lbs. /ft. (2.24 kg/m)
Density	3.4 lbs. /ft. ³ (55 kg/cm ³ .)
Filler material	100% coconut fiber (mattress coir fiber)
Size	
Length	15 ft. (4.6 m)
Diameter	9 in (23 cm)
Outer netting	Bristle coir twine
Mesh opening	2 in X 2 in (5 cm x 5 cm)
Tensile strength / twine	60 lbs. (267 N)



155 Andrew Drive, Stockbridge, GA 30281

1 800 760 3215

Tel: 770 506 8211 Fax: 770 506 0391

E-mail: rolanka@rolanka.com

Web: www.rolanka.com

DOT DBE Certified